

Keywords: Airslide fabric, air slide fabrics, air slide belt, air permeable fabric, fluidizing fabric, air slide belt fabric, air slide cloth, air slide belt, air slide filter cloth, aero cloth, air slide canvas, solid woven air slide material

China Sunrise Machinery – Air Slide Fabric

www.air-slide-fabric.com

86-513-88820117

Airslide Fabric Technical Specification

Inspection Standard:	Q/320621CBC01-2011
Material:	Polyester Staple Fiber
Weight (g/m2):	3800-3900
Lenght (m):	20-100
Width (mm):	250,270,480,580
Thickness (mm):	5-8
Breathability (2m3/m2 min)	800pa-1200pa
Breathability (<3m3/m2 min)	<2000pa
Breaking Strength (N/mm)	Warp Direction ≥ 5600N/mm
	Weft Direction ≥ 4400N/mm
Operating Temperature ($^\circ \! \mathbb{C}$)	Continuous Operation 220,
	Instant Operation 250
SKU	m²
Availability:	In Stock

• Specification sheet of polyester airslide fabric:

Ps: Tolerance of thickness: +/- 0.3mm , gram weight: +/- 3%, air permeability: +/- 10%.

•**Porosity:** the pores are suitable, uniform distribution, distribution of gas dispersion is high, less affected by the thickness of grain layer;

•Corrosion resistance: a certain strength, wear-resistant, suitable for ordinary portland cement and fly, cement, PVC, alumina powder, calcium oxide, soda ash, etc .; physical and chemical properties of stability;

•Through the nature: only through the gas, can not through the powder; moisture absorption, low adhesion, smooth surface, easy powder flow, long-term use is not blocked, and easy to restore breathability;

•Inspection report: issue test report.

Common specifications are 250mm 270mm 480mm 580mm.